

TONOPAH SPEEDWAY

2010 MINI STOCK RULES

- 1.) Mini Stock Division will be open to all 4 cylinder cars and trucks, American or Foreign.
- 2.) Engine and Body must be from the same Manufacturers. Example Ford to Ford, GM to GM. Engines must remain stock. No engine modifications allowed. No limited production performance models allowed. No racing parts allowed. No power chips allowed. Diagnostic plugs can not be removed. Front engine cars and trucks only. No turbos. No rotary engines. No after market headers, no head milling allowed. Compression must be stock for that make and model. No exceptions. Street Holley and Weber Carbs ok, no racing carbs. Stock cams only. Pump gas only. Any mini stock that dominates or walks away may be subject to adding weight at anytime, per techs discretion.
- 3.) Tires: Street tires only. No racing tires aftermarket steel wheel ok . No aluminum wheels, even if aluminum wheels came stock with the car. D.O.T. street tires only. No 50 series tires. 8 inch wheel max.
- 4.) Roll cage: 4 point roll cage minimum 1.5 x .095 inch tubing. Must have 3 horizontal driver side door bars and a minimum of 2 horizontal door bars on passenger side .095 tubing minimum.
- 5.) Interior: All glass, carpet and plastics must be removed from inside and outside the car (stock dash may be retained). Batteries, if inside drivers compartment must be in a sealed marine type box, securely mounted to the floor.
- 6.) Seats: May use stock seat. Racing seat recommended attached to cage. Must have minimum of a 4-point harness, 5 point recommended. No stock seat belts. Belts may be 4 years old max. or newer.
- 7.) Suspension: No suspension modification allowed. No racing springs. No racing shocks, no lowering blocks etc All shocks must remain in stock location. Can heat springs for set up. Stock suspension may be reinforced but must remain in original mounting position.
- 8.) Bodies: Must use stock bodies. No aftermarket racing bodies or body modifications. No spoilers or hood scoops. No removal of floor pan or

firewalls allowed. May gut fenders, hood, roof, etc ... No open roofs period ...•.

8a.) Cars will weigh 1500 # min. without driver.

9.) Brakes: Cars must have minimum 4 working brakes at all times.

10.) Bumpers: Cars must use stock bumpers and must have two safety chains from frame to bumper, front and rear. Tubular bumpers allowed. No bars to extend beyond the bumpers. 2 – 1 1/2 x 1.20 max. No wider than the body and attached to the body with plate.

11.) Steering: Stock Quick release steering wheel allowed

12.) Safety: See track rules. Driver side window net mandatory. 4 years old or newer. Front screen required in front of driver. See track rules regarding fire extinguishers. Can use stock gas tanks as long as safely mounted in car.